

1. Identification of the Substance / Mixture and of the Company

1.1 PRODUCT IDENTIFICATION

Xypex Cementitious Products
Concentrate
Modified
DS-1 & DS-2
C-500 & C-500 NF
Admix C-1000 & C-1000 NF
Admix C-500 NF Red & Admix C-1000 Red
Admix C-2000 & C-2000 NF
Megamix I & Megamix II
FCM 80 (powder component)
Patch'n Plug
RestoraTop 50, 100 & 200

1.2 PRODUCT USE

Waterproofing and protection of concrete

1.3 COMPANY IDENTIFICATION

Xypex Chemical Corporation
13731 Mayfield Place
Richmond, B.C., Canada
Tel: 604-273-5265 or 800-961-4477
Fax: 604-270-0451
E-mail: info@xypex.com
Web: www.xypex.com

1.4 EMERGENCY TELEPHONE NUMBERS

During normal Pacific Standard Time (PST)
800-961-4477 or 604-273-5265
All other times, and in times of unavailability, contact your local emergency services.

2. Hazards Identification

2.1 CLASSIFICATION OF THE MIXTURE

2.1.1 Classification In Accordance With GHS (5th Edition)

Skin Irrit. 2: H315	Causes skin irritation.
Eye Dam. 1: H318	Causes serious eye damage.
Skin Sens. 1: H317	May cause an allergic skin reaction.
STOT SE 3: H335	May cause respiratory irritation.
STOT RE 2: H373	May cause damage to respiratory organs through prolonged or repeated exposure.

2.2 LABEL ELEMENTS: in Accordance with GHS (5th Edition)



DANGER

2.3 HAZARD STATEMENTS

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to respiratory organs through prolonged or repeated exposure.

2.4 PRECAUTIONARY STATEMENTS

P280 Wear protective gloves / protective clothing / eye protection / face protection & approved duct masks.

P260 Do not breathe dust.

P264 Wash thoroughly after handling.

2.5 RESPONSIVE PRECAUTIONARY STATEMENTS

P260 Do not breathe dust

P264 Wash thoroughly after handling

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor / physician.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

3. Composition / Information on Ingredients

Hazardous Ingredients	%	CAS. No.	Classification According to GHS (5th Edition)
Portland Cement	35 - 60%	65997-15-1	Skin Irrit. 2: H315 Skin Sens. 1: H317 Eye Dam. 1: H318 STOT SE 3: H335
Alkaline Earth Compounds (calcium dihydroxide)	5 - 20%	1305-62-0	Skin Irrit. 2: H315 Eye Dam. 1: H318 STOT SE 3: H335
Silica Sand (< 0.005 % (w/w) 10 µm respirable silica)	30 - 40%	14808-60-7	STOT RE 2: H373

4. First Aid Measures

4.1 DESCRIPTION OF FIRST AID MEASURES

When seeking medical advice take this safety data sheet with you.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Dust in throat and nasal passages should clear spontaneously. If not, irrigate nose and throat with clean water for at least 20 minutes. Seek immediate professional medical attention.

EYE CONTACT: IF IN EYES – Quickly and gently blot away any dry powder. Irrigate cautiously with large amounts of water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub eyes as this may cause additional irritation or damage. Seek immediate professional medical attention if irritation persists.

SKIN CONTACT: Quickly and gently blot away any dry powder. Under running water, remove contaminated clothing, shoes and leather goods. Continuously flush contaminated area with lukewarm, gently flowing water for at least 60 minutes. If skin irritation or rash occurs, seek medical advice / attention.

INGESTION: Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If conscious, wash out mouth with clean water. Drink 1 cup (240 - 300 ml) of water followed by dilution with milk if available. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing. Seek immediate professional medical assistance and contact a poison centre.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

ACUTE: Irritation to skin and mucous membranes.

DELAYED: Precautions should be taken to ensure that dust is not inhaled; however, long-term exposure to high levels of dust may result in damage to the lungs.

4.3 IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

Move person to fresh air and away from exposure. Wash and clean eyes or skin as described in 4.1. Ensure eyewash facilities are available.

5. Firefighting Measures

5.1 EXTINGUISHING MEDIA

Xypex Cementitious Products are not flammable and are not subject to explosion.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

No hazardous combustion products.

Alkaline earth compounds will cause explosive decomposition of maleic anhydride, nitroalkanes and nitroparaffins, in the presence of water, form salts with inorganic salts and with inorganic bases. The dry salts are explosive.

5.3 ADVICE FOR FIREFIGHTERS

No need for specialist protective equipment for firefighters. Prior to using the product liaise with local fire authority for confirmation of best and most current form of firefighting equipment for the product.

6. Accidental Release Measures

6.1 PERSONAL PROTECTIVE MEASURES

Always wear full protective equipment as referred to under Section 8.2.2 to prevent any contamination of skin, eyes, respiratory system and personal clothing. Ensure adequate measures are in place to prevent airborne dust. Avoid airborne dust generation.

6.2 ENVIRONMENT PROTECTION MEASURES

Do not allow product into drains or water courses. Any spillages into watercourses must be alerted to the Environment Agency or other regulatory body.

6.3 METHODS FOR CLEANING UP

At all times avoid inhalation of product and contact with skin and eyes. Contain the spillage. Keep the material dry if possible. Wear full personal protective equipment when cleaning up, whatever method is chosen. When the product is in a dry state, avoid airborne dust generation when cleaning up. Avoid dry sweeping. Examples of cleanup methods when in dry state are:

(A) Using a vacuum cleaner (Industrial portable units), equipped with high efficiency particulate filters (HEPA filter) or equivalent technique.

(B) Wipe up the dust by mopping, wet brushing or water sprays or hoses with a fine mist to avoid the dust becoming airborne and remove slurry. Ensure drains are covered.

If the product has become wet, clean up and place in watertight container. Allow material to dry and solidify before disposal. Check current regulations before disposing of spillage, whether in dry state or not.

7. Handling & Storage

7.1 HANDLING

Avoid all types of dust generation; particularly the creation of respirable dust. At all times avoid inhalation of product and contact with skin and eyes. Carrying the product may cause back injuries, strains, sprains or the like. Use correct handling techniques to avoid injury. Use handling equipment and controls if necessary to avoid injury. If in doubt, contact your local health and safety body for further guidance on annual handling. Always wear sufficient and full protective equipment and suitable clothing when handling the product. General – During work avoid kneeling in the product. If kneeling is absolutely necessary then appropriate impervious waterproof personal protective equipment must be worn.

Ensure adequate ventilation and have ventilation equipment available if required due to possibility of generation of airborne dust.

Do not eat, drink or smoke when handling or applying product. Remove contaminated clothing and protective equipment before entering eating areas.

Avoid mishandling of pails of bags so as to prevent accidental bursting and creation of dust.

7.2 STORAGE

P402 + P232 + 233 Store in a dry place. Protect from moisture. Keep container tightly closed.

Store this product in a draught free environment, clear of the ground, avoiding humid conditions and extremes of temperature (minimum lower temperature of 7°C (45°F). The product should be used within 12 months of the date of production; product should not have been exposed to the atmosphere prior to use.

Any product that is stacked should be done so in a stable manner, and to a safe height. The stacking of product should be done in such a manner that it does not create any risk of product falling and accidentally bursting the packaging open.

This product contains Portland cement and thus Chromium (VI) and may produce an allergic reaction. The cement in this product may contain a reducing agent; the effectiveness of the reducing agent reduces with time.

8. Exposure Control / Personal Protection

8.1 CONTROL PARAMETERS

P260 Do not breathe dust.

P401 Store in original containers.

Substance	CAS No	Regulatory Limits			Recommended Limits	
		OSHA PEL		Cal/OSHA PEL (as of 4/26/13)	NIOSH REL (as of 4/26/13)	ACGIH 2015 TLV
		ppm	mg/m	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
Calcium hydroxide	1305-62-0					
Total dust			15	5 mg/m ³	5 mg/m ³	5 mg/m ³
Respirable fraction			5			
Portland cement	65997-15-1					
Total dust			15	10 mg/m ³	10 mg/m ³	
Respirable fraction			5	5 mg/m ³	5 mg/m ³	1 mg/m (no asbestos and < 1% crystalline silica)
Silica: Crystalline	14808-60-7					0.025 (resp.) for a-quartz and cristobalite mg/m ³
Quartz (Respirable)		250(h) (%SiO ₂ +5)	10 mg/m (%SiO ₂ +2)	0.1 mg/m ³	Ca 0.05 mg/m ³	
Quartz (Total Dust)			30 mg/m (%SiO ₂ +2)			

Please refer to OSHA website for additional information.

Please note that the % of respirable crystalline silica in the silica sand is < 0.005 % but some processes and uses may increase this fraction.

8.2 EXPOSURE CONTROLS

8.2.1 Appropriate Engineering Controls

Provide adequate and suitable ventilation / ventilation equipment when handling product, to maintain dust below OES. All ventilation systems should be filtered before discharge to atmosphere. Isolate personnel from dusty areas.

Do not eat, drink or smoke when working with the product to avoid contact with skin or mouth. Immediately after working with the product, workers should wash or shower or use skin moisturizers. Remove contaminated clothing, footwear, watches, etc... and clean thoroughly before re-using.

8.2.2 *Personal Protection Equipment*

- P280 Wear protective gloves / protective clothing / eye protection / face protection.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

Skin Protection – Use impervious, abrasion and alkali resistant gloves, enclosed rubber boots that resist powder and liquid penetration, closed long-sleeved impervious protective clothing that protects skin from contact. Close all fittings at opening.

Eye Protection – Wear safety goggles / glasses at all times when handling the product. Ensure the goggles / glasses have suitable side protection, are wide vision, and that there is no risk of product particles being able to enter the eye(s).

Respiratory Protection – Always use respiratory protection. Inhalation of product dust must be avoided at all times. Use an APPROVED NIOSH dust mask. Respiratory protective equipment must be in compliance with relevant national legislation. It is good practice to conduct fit-testing when selecting respiratory protective equipment.

Additional safety precautions may include the provision a shower facility.

8.2.3 *Environmental Exposure Controls*

According to available technology that limit dust dispersion into the environment.

9. Physical & Chemical Properties

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

<i>Appearance</i>	Grey particulate powder
<i>Odour</i>	None
<i>pH</i>	pH 9.1 – 9.8 (EPA method 2 parts water to 1 part powder by volume weight)
<i>Melting / Freezing Point</i>	Not applicable
<i>Initial Boiling Point and Range</i>	Not applicable
<i>Flash Point</i>	Not applicable
<i>Evaporation Rate</i>	Not applicable
<i>Flammability Upper / Lower flammability / Explosive Limits</i>	Not applicable
<i>Vapour Pressure</i>	Not applicable
<i>Vapour Density</i>	Not applicable
<i>Solubility</i>	Powder forms slurry with water, hardens over time
<i>Auto-ignition Temperature</i>	Not applicable
<i>Decomposition Temperature</i>	Alkaline earth compounds: 580°C
<i>Viscosity</i>	Not applicable
<i>Explosive Properties</i>	Not applicable
<i>Oxidizing Properties</i>	Not applicable
<i>Specific Gravity</i>	2.0 to 2.8 (water = 1)

10. Stability & Reactivity

10.1 REACTIVITY

Alkaline earth compounds react vigorously with strong acids. They also attack aluminum, lead and brass in the presence of moisture.

In the presence of water, calcium aluminates react chemically and harden to form stable calcium aluminate hydrates. This reaction is exo-thermal and may last up to 24 hours. The total heat released is < 500 kJ/kg.

10.2 CHEMICAL STABILITY

The product is chemically stable. When mixed with water it will harden, with time, into a stable mass. Products may liberate Carbon Monoxide or Carbon Dioxide.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Alkaline earth compounds will cause explosive decomposition of maleic anhydride, nitroalkanes and nitroparaffins, in the presence of water, form salts with inorganic salts and with inorganic bases. The dry salts are explosive.

Alkaline earth compound is stable up to 580°C. Alkaline earth compounds decompose with loss of water at approximately 580°C to form Calcium Oxide.

10.4 CONDITIONS TO AVOID

Avoid humid and drafty environments during storage. Also avoid storage temperatures below 7°C.

10.5 INCOMPATIBLE MATERIALS

Products are incompatible with strong acids.

It should be noted that the uncontrolled use of aluminum powder in wet cement should be avoided as hydrogen is produced.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

None known.

11. Toxicological Information

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Dermal Toxicity: The cement incorporated with the other ingredients in this product has been subject to a Limit test. (Limit test, rabbit, 24 hours contact, 2,000 mg/kg body weight – no lethality.) Calcium dihydroxide is not acutely toxic. Rabbit dermal LD50 > 2,500 mg/kg/bw.

Acute Oral Toxicity: May cause irritation to the gastrointestinal tract. Calcium dihydroxide is not acutely toxic. Rat oral LD50 > 2,000 mg/kg/bw.

Acute Inhalation Toxicity: The product may irritate the throat and respiratory tract. Inhalation may lead to irritation, inflammation or burns. Coughing, sneezing and shortness of breath may occur following exposures in excess of occupational exposure limits.

Skin Corrosion / Irritation: When skin is exposed to the product in its dry or wet state, thickening, cracking or fissuring of the skin may occur. Prolonged contact in combination with abrasion can cause severe burns.

Portland cement and alkaline earth compound are an irritant to skin. Ingredients are dermal irritants and dermatitis may develop following exposure.

Cement may have an irritating effect on moist skin (due to transpiration of humidity) after prolonged contact. Prolonged skin contact with wet cement or fresh concrete may cause serious burns because they develop without pain being felt. Repeated skin contact with wet cement may cause dermatitis.

This mixture contains < 2 ppm Chromium (VI), which is a skin irritant.

Serious Eye Damage / Irritation: Direct contact with product may cause corneal damage by mechanical stress, immediate or delayed irritation or inflammation. Direct contact either in dry or wet form may cause effects ranging from moderate eye irritation (eg. conjunctivitis or blepharitis) to chemical burns or blindness.

Skin Sensitization: This product contains Portland cement which is classified as a skin sensitizer.

Contact Dermatitis / Sensitizing Effects: Prolonged and repeated skin contact with Alkaline earth products may cause dermatitis.

Some individuals may exhibit eczema upon exposure to wet cementitious products, caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The response may appear in a variety of forms ranging from a mild rash to severe dermatitis and is a combination of those two mechanisms. An exact diagnosis is often difficult to assess.

Germ Cell Mutagenicity: With the exception of Chromium (VI) (< 2 ppm) in the Portland cement, none of the individual substances in this mixture are classified as mutagenic.

Carcinogenicity: This product contains silica sand and this form of silica is not classified as carcinogenic due to its large particle size. However, prolonged and / or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated.

IARC (1997) has concluded that there is 'sufficient evidence for the carcinogenicity of inhaled crystalline silica in the form of quartz and cristobalite in certain industrial circumstances, but that the carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of polymorphs'.

Principle symptoms of lung fibrosis (commonly referred to as silicosis) are cough and breathlessness. Occupational exposure to respirable dust and respirable crystalline silica dust should be monitored and controlled.

Reproductive Toxicity: None of the individual substances in this mixture are classified as reproductive toxicants.

Specific Target Organ Toxicity – Single Exposure: Inhalation of dust can result in damage to the respiratory tract.

Specific Target Organ Toxicity – Repeat Exposure: Prolonged or repeated inhalation exposure may cause damage to the lungs, including chronic obstructive pulmonary disease (COPD).

Certain ingredients within these products do give potential for generation of respirable dust during handling and use. The dust may contain respirable crystalline silica.

Prolonged or frequent or excessive exposure to respirable crystalline silica dust, cement dust and alkaline earth products may cause respiratory disease, lung disease, lung and respiratory tract damage, ulceration and perforation of the nasal septum, pneumonitis and other serious bad health effects.

The excessive inhalation of crystalline silica dust may result in respiratory disease, including silicosis, pneumoconiosis and pulmonary fibrosis.

11.2 ASPIRATION HAZARD

No data available.

11.3 LIKELY ROUTES OF EXPOSURE

Inhalation: YES

Skin – Eyes: YES

Ingestion: NO – except in accidental cases

11.4 POTENTIAL HEALTH EFFECTS

The product may irritate and burn the throat and respiratory tract. Coughing, sneezing and shortness of breath may occur following exposures in excess of occupational exposure limits. Causes skin irritation and is a severe eye irritant.

Chronic exposure to respirable dust in excess of occupational exposure limits may cause coughing, shortness of breath and may cause chronic obstructive lung disease (COPD).

11.5 MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Inhaling dust may aggravate existing respiratory system disease(s) and / or medical conditions such as emphysema or asthma and / or existing skin and / or eye conditions.

12. Ecological Information

12.1 ECOTOXICITY

Do not allow the material to enter water course. If water is contaminated inform the relevant authorities immediately. The addition of a significant amount of cementitious products to water may cause a rise in the pH value and therefore may be toxic to aquatic life under certain circumstances.

Alkaline conditions may also have effects on vegetation.

The following toxicity values are available for calcium dihydroxide:

LC50 (96h) for freshwater / marine fish: 50.6 mg/l and 457 mg/l

EC50 (48h) for freshwater invertebrates: 49.1 mg/l

LD50 (96h) for marine water invertebrates: 158 mg/l

EC50 (72h) for freshwater algae: 184.57 mg/l and the NOEC is 48 mg/l

NOEC (14d) for marine water invertebrates: 32 mg/l

EC10/LC10 or NOEC for soil macro-organisms: 2,000 mg/kg soil dw and for micro-organisms is 12,000 mg/kg/ soil dw

NOEC (21d) for terrestrial plants: 1,080 mg/kg

12.2 PERSISTENCE AND DEGRADABILITY

Alkaline earth material is non bio-degradable; it reacts with atmosphere and dissolved carbon dioxide to form calcium carbonate (chalk).

12.3 BIO ACCUMULATIVE POTENTIAL

None of the substances in this mixture are known to bioaccumulate.

12.4 MOBILITY IN SOIL

Not known.

12.5 RESULTS OF PBT AND VPVB ASSESSMENT

This mixture does not contain any substances that are assessed to be PBT or vPvB.

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS

Avoid creation of airborne and respirable dust when disposing of product.

Product – Unused Residue or Dry Spillage

Pick up dry and put in containers. Mark container clearly. In case of disposal, harden with water to avoid dust creation. Dispose of at a licensed waste facility accepting cementitious and alkaline earth based waste. Dispose of all materials in accordance with current local regulations / legislation.

Product – Slurries

Allow to harden. Avoid entry into sewage and drainage systems or into bodies of water and dispose of as indicated for hardened product.

Product – After Addition of Water, Hardened

Dispose of at a licensed waste facility accepting cementitious and alkaline earth based waste. Dispose of all materials in accordance with current regulations / legislation. Avoid entry into sewage and drainage systems or into bodies of water.

13.2 PACKAGING

Completely empty packaging and process it according to current regulations / legislation.

14. Transportation Information

The product is not classified as hazardous for transport purposes.

15. Regulatory Information

GHS
WHMIS
OSHA

16. Other Information

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service Number
OEL	Occupational Exposure Limit
TWA	Time Weighted Averages
PEL	Permissible Exposure Limit
MEL	Maximum Exposure Limit
LC	Lethal Concentration
LD	Lethal Dose
UEL	Upper Explosion Limit
LEL	Lower Explosion Limit
PPE	Personal Protective Equipment
EC50	Median effective concentration
LC50	Median lethal concentration
LD50	Median lethal dose
NOEC	No observable effect concentration
WHMIS	Workplace Hazardous Materials Information System

Hazard Statements In Full

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H373	May cause damage to respiratory organs through prolonged or repeated exposure.

Precautionary Statements In Full

P260	Do not breathe dust.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash ... thoroughly after handling.

Responsive Precautionary Statements

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor / physician.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332+ P313	If skin irritation or rash occurs: Get medical advice / attention.
P362	Take off contaminated clothing and wash before reuse.
P501	Dispose of contents / container to ...
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P314	Get medical advice / attention if you feel unwell.

Revisions Date: January 15, 2019 / Rev. No. 1

Disclaimer: Xypex Chemical Corporation believes the information contained herein is accurate; however, Xypex makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state, provincial or local laws or regulations. Any party using these products should review all such laws, rules, regulations prior to use, including, but not limited to the US and Canada Federal, Provincial and State regulations.